

Package: corncob (via r-universe)

October 9, 2026

Title Count Regression for Correlated Observations with the Beta-Binomial

Version 0.4.3

Description Statistical modeling for correlated count data using the beta-binomial distribution, described in Martin et al. (2020) <[doi:10.1214/19-AOAS1283](https://doi.org/10.1214/19-AOAS1283)>. It allows for both mean and overdispersion covariates.

URL <https://github.com/statdivlab/corncob>,
<https://statdivlab.github.io/corncob/>

BugReports <https://github.com/statdivlab/corncob/issues>

Depends R (>= 3.2)

License GPL (>= 2)

Imports stats, utils, VGAM, numDeriv, ggplot2, trust, dplyr, magrittr, detectseparation, scales, rlang

Encoding UTF-8

LazyData true

RoxygenNote 7.3.3

Suggests knitr, rmarkdown, testthat, covr, limma, slam, R.rsp, optimx, phyloseq, SummarizedExperiment

VignetteBuilder knitr

Config/pak/sysreqs cmake make libuv1-dev

Repository <https://statdivlab.r-universe.dev>

Date/Publication 2025-11-13 18:19:04 UTC

RemoteUrl <https://github.com/statdivlab/corncob>

RemoteRef HEAD

RemoteSha d7ac4c8a3f757eef6c7d8006431494528ead8e92

Contents

corncob-package	3
bbdml	3
checkNested	5
clean_taxa_names	6
clean_taxa_names_se	6
contrastsTest	7
convert_phylo	9
convert_sumexp	10
coth	10
dbetabin	11
dbetabin_neg	11
dbetabinom_cts	12
differentialTest	13
doBoot	15
fishZ	16
genInits	17
getRestrictionTerms	18
gr_full	18
HDIbetabinom	19
hessian	20
ibd_phylo_otu	20
ibd_phylo_sample	21
ibd_phylo_taxa	21
invfishZ	22
invlogit	22
logit	23
lrtest	24
objfun	24
otu_to_taxonomy	25
otu_to_taxonomy_se	26
pbLRT	26
pbRao	27
pbWald	28
plot.bbdml	28
plot.differentialTest	30
print.bbdml	31
print.differentialTest	31
print.summary.bbdml	32
qbetabinom	33
raotest	34
sand_vcov	34
sandSE	35
score	36
simulate.bbdml	36
soil_phylo_otu	37
soil_phylo_sample	38

soil_phylo_taxa	38
soil_phylum_contrasts_otu	39
soil_phylum_contrasts_sample	40
soil_phylum_small_otu	40
soil_phylum_small_otu1	41
soil_phylum_small_sample	42
summary.bbdml	43
waldchisq	43
waldchisq_test	45
walddt	46
warn_phyloseq	46
warn_sumexp	47
Index	48

corncob-package	<i>Corncob package documentation.</i>
-----------------	---------------------------------------

Description

Corncob provides methods for estimating and plotting count data. Specifically, corncob is designed to account for the challenges of modeling sequencing data from microbial abundance studies.

Details

For details on the model implemented in this package, see Martin et al. (2020) <doi:10.1214/19-AOAS1283>.

The development version of the package will be maintained on <https://github.com/statdivlab/corncob>.

Value

No return value. Created for documentation.

bbdml	<i>Maximum Likelihood for the Beta-binomial Distribution</i>
-------	--

Description

Maximum Likelihood for the Beta-binomial Distribution

Usage

```
bbdml(
  formula,
  phi.formula,
  data,
  link = "logit",
  phi.link = "logit",
  method = "trust",
  control = list(maxit = 1000, reltol = 1e-14),
  numerical = FALSE,
  nstart = 1,
  inits = NULL,
  allow_noninteger = FALSE,
  robust = FALSE,
  ...
)
```

Arguments

<code>formula</code>	an object of class <code>formula</code> : a symbolic description of the model to be fitted to the abundance
<code>phi.formula</code>	an object of class <code>formula</code> without the response: a symbolic description of the model to be fitted to the dispersion
<code>data</code>	a data frame, <code>phyloseq</code> , or <code>SummarizedExperiment</code> object containing the variables in the models
<code>link</code>	link function for abundance covariates, defaults to <code>"logit"</code>
<code>phi.link</code>	link function for dispersion covariates, defaults to <code>"logit"</code>
<code>method</code>	optimization method, defaults to <code>"trust"</code> , or see optimr for other options
<code>control</code>	optimization control parameters (see optimr)
<code>numerical</code>	Boolean. Defaults to <code>FALSE</code> . Indicator of whether to use the numeric Hessian (not recommended).
<code>nstart</code>	Integer. Defaults to 1. Number of starts for optimization.
<code>inits</code>	Optional initializations as rows of a matrix. Defaults to <code>NULL</code> .
<code>allow_noninteger</code>	Boolean. Defaults to <code>FALSE</code> . Should noninteger W's and M's be allowed? This behavior was not permitted prior to v4.1, needs to be explicitly allowed.
<code>robust</code>	Should robust standard errors be returned? If not, model-based standard errors are used. Logical, defaults to <code>FALSE</code> .
<code>...</code>	Optional additional arguments for optimr or trust

Value

An object of class `bbdml`.

Examples

```
# data frame example
data(soil_phylum_small_otu1)
bbdml(formula = cbind(W, M - W) ~ DayAmdmt,
phi.formula = ~ DayAmdmt,
data = soil_phylum_small_otu1)

# phyloseq example (only run this if you have phyloseq installed)
## Not run:
data(soil_phylum_small_sample)
data(soil_phylum_small_otu)
data_phylo <- phyloseq::phyloseq(phyloseq::sample_data(soil_phylum_small_sample),
phyloseq::otu_table(soil_phylum_small_otu, taxa_are_rows = TRUE))
bbdml(formula = Proteobacteria ~ DayAmdmt,
phi.formula = ~ DayAmdmt,
data = data_phylo)

## End(Not run)
```

checkNested	<i>Check for nested models</i>
-------------	--------------------------------

Description

Check for nested models

Usage

```
checkNested(mod, mod_null)
```

Arguments

mod	an object of class bbdml
mod_null	an object of class bbdml

Value

TRUE if mod_null is nested within mod, otherwise it throws an error.

Examples

```
data(soil_phylum_small_otu1)
mod1 <- bbdml(formula = cbind(W, M - W) ~ DayAmdmt,
phi.formula = ~ DayAmdmt,
data = soil_phylum_small_otu1)

mod2 <- bbdml(formula = cbind(W, M - W) ~ 1,
phi.formula = ~ 1,
```

```
data = soil_phylum_small_otu1)

checkNested(mod1, mod2)
```

clean_taxa_names	<i>Rename taxa</i>
------------------	--------------------

Description

Renames taxa to have short human-readable names

Usage

```
clean_taxa_names(x, name = "OTU")
```

Arguments

- x Object of class phyloseq
- name Character, defaults to "OTU". Optional. String to use in every taxa name.

Details

The original taxa names are saved as the original_names attribute. See the example for an example of how to access the original names.

Value

Object of class phyloseq, with taxa renamed (defaults to OTU1, OTU2, ...), with the original taxa names saved as an attribute.

clean_taxa_names_se	<i>Rename taxa</i>
---------------------	--------------------

Description

Renames taxa to have short human-readable names

Usage

```
clean_taxa_names_se(x, name = "OTU")
```

Arguments

- x Object of class SummarizedExperiment
- name Character, defaults to "OTU". Optional. String to use in every taxa name.

Details

The original taxa names are saved as the `original_names` attribute. See the example for an example of how to access the original names.

Value

Object of class `SummarizedExperiment`, with taxa renamed (defaults to OTU1, OTU2, ...), with the original taxa names saved as an attribute.

<code>contrastsTest</code>	<i>Identify differentially-abundant and differentially-variable taxa using contrasts</i>
----------------------------	--

Description

Identify differentially-abundant and differentially-variable taxa using contrasts

Usage

```
contrastsTest(
  formula,
  phi.formula,
  contrasts_DA = NULL,
  contrasts_DV = NULL,
  data,
  link = "logit",
  phi.link = "logit",
  sample_data = NULL,
  taxa_are_rows = TRUE,
  filter_discriminant = TRUE,
  fdr_cutoff = 0.05,
  fdr = "fdr",
  inits = NULL,
  try_only = NULL,
  ...
)
```

Arguments

<code>formula</code>	an object of class <code>formula</code> without the response: a symbolic description of the model to be fitted to the abundance
<code>phi.formula</code>	an object of class <code>formula</code> without the response: a symbolic description of the model to be fitted to the dispersion
<code>contrasts_DA</code>	List. Optional. Constructs a contrast matrix. List elements should be characters specifying contrasts in the parameters within <code>formula</code> . Note that this is only available with "Wald" value for test. Must include at least one of <code>contrasts_DA</code> or <code>contrasts_DV</code> .

contrasts_DV	List. Optional. Constructs a contrast matrix. List elements should be characters specifying contrasts in the parameters within <code>phi.formula</code> . Note that this is only available with "Wald" value for test. Must include at least one of <code>contrasts_DA</code> or <code>contrasts_DV</code> .
data	a data frame containing the OTU table, or phyloseq object containing the variables in the models
link	link function for abundance covariates, defaults to "logit"
phi.link	link function for dispersion covariates, defaults to "logit"
sample_data	Data frame or matrix. Defaults to NULL. If data is a data frame or matrix, this must be included as covariates/sample data.
taxa_are_rows	Boolean. Optional. If data is a data frame or matrix, this indicates whether taxa are rows. Defaults to TRUE.
filter_discriminant	Boolean. Defaults to TRUE. If FALSE, discriminant taxa will not be filtered out.
fdr_cutoff	Integer. Defaults to 0.05. Desired type 1 error rate
fdr	Character. Defaults to "fdr". False discovery rate control method, see p.adjust for more options.
inits	Optional initializations for model fit using formula and <code>phi.formula</code> as rows of a matrix. Defaults to NULL.
try_only	Optional numeric. Will try only the <code>try_only</code> taxa, specified either via numeric input or character taxa names. Useful for speed when troubleshooting. Defaults to NULL, testing all taxa.
...	Optional additional arguments for bbdml

Details

This function uses contrast matrices to test for differential abundance and differential variability using a Wald-type chi-squared test. To use a formula implementation, see [differentialTest](#).

Value

An object of class `contrastsTest`. List with elements `p` containing the p-values for each contrast, `p_fdr` containing the p-values after false discovery rate control, `significant_taxa` containing the taxa names of the statistically significant taxa, `contrasts_DA` containing the contrast matrix for parameters associated with the abundance, `contrasts_DV` containing the contrast matrix for parameters associated with the dispersion, `discriminant_taxa_DA` containing the taxa for which at least one covariate associated with the abundance was perfectly discriminant, `discriminant_taxa_DV` containing the taxa for which at least one covariate associated with the dispersion was perfectly discriminant, and `data` containing the data used to fit the models.

Examples

```
# data frame example
# note that this function will only run if the `limma` package is installed
limma_install <- try(find.package("limma"), silent = TRUE)
if (!(inherits(limma_install, "try-error"))) {
```

```

data(soil_phylum_contrasts_sample)
data(soil_phylum_contrasts_otu)
da_analysis <- contrastsTest(formula = ~ DayAmdmt,
                             phi.formula = ~ DayAmdmt,
                             contrasts_DA = list("DayAmdmt21 - DayAmdmt11",
                                                  "DayAmdmt22 - DayAmdmt21"),
                             data = soil_phylum_contrasts_otu,
                             sample_data = soil_phylum_contrasts_sample,
                             fdr_cutoff = 0.05,
                             try_only = 1:5)
}

# phyloseq example (only run if you have phyloseq installed)
## Not run:
contrasts_phylo <- phyloseq::phyloseq(phyloseq::sample_data(soil_phylum_contrasts_sample),
phyloseq::otu_table(soil_phylum_contrasts_otu, taxa_are_rows = TRUE))
da_analysis <- contrastsTest(formula = ~ DayAmdmt,
                             phi.formula = ~ DayAmdmt,
                             contrasts_DA = list("DayAmdmt21 - DayAmdmt11",
                                                  "DayAmdmt22 - DayAmdmt21"),
                             data = contrasts_phylo,
                             fdr_cutoff = 0.05,
                             try_only = 1:5)

## End(Not run)

```

convert_phylo

Function to subset and convert phyloseq data

Description

Function to subset and convert phyloseq data

Usage

```
convert_phylo(data, select)
```

Arguments

data	a phyloseq object
select	Name of OTU or taxa to select, must match taxa name in data

Value

A data.frame object, with elements W as the observed counts, M as the sequencing depth, and the sample data with their original names.

convert_sumexp	<i>Function to subset and convert SummarizedExperiment data</i>
----------------	---

Description

Function to subset and convert SummarizedExperiment data

Usage

```
convert_sumexp(data, select)
```

Arguments

data	a SummarizedExperiment object
select	Name of OTU or taxa to select, must match taxa name in data

Value

A data.frame object, with elements W as the observed counts, M as the sequencing depth, and the sample data with their original names.

coth	<i>Hyperbolic cotangent transformation</i>
------	--

Description

Hyperbolic cotangent transformation

Usage

```
coth(x)
```

Arguments

x	data
---	------

Value

Hyperbolic cotangent transformation of x

Examples

```
x <- .5  
coth(x)
```

dbetabin	<i>Betabinomial density</i>
----------	-----------------------------

Description

Betabinomial density

Usage

```
dbetabin(theta, W, M, X, X_star, np, npstar, link, phi.link, logpar = TRUE)
```

Arguments

theta	Numeric vector. Parameters associated with X and X_{star}
W	Numeric vector of counts
M	Numeric vector of sequencing depth
X	Matrix of covariates associated with abundance (including intercept)
X_star	Matrix of covariates associated with dispersion (including intercept)
np	Number of covariates associated with abundance (including intercept)
npstar	Number of covariates associated with dispersion (including intercept)
link	link function for abundance covariates
phi.link	link function for dispersion covariates
logpar	Boolean. Defaults to TRUE. Indicator of whether to return log-likelihood.

Value

Negative beta-binomial (log-)likelihood

dbetabin_neg	<i>Negative betabinomial density</i>
--------------	--------------------------------------

Description

Created as a convenient helper function for optimization. Not intended for users.

Usage

```
dbetabin_neg(theta, W, M, X, X_star, np, npstar, link, phi.link, logpar = TRUE)
```

Arguments

theta	Numeric vector. Parameters associated with X and X_{star}
W	Numeric vector of counts
M	Numeric vector of sequencing depth
X	Matrix of covariates associated with abundance (including intercept)
X_star	Matrix of covariates associated with dispersion (including intercept)
np	Number of covariates associated with abundance (including intercept)
npstar	Number of covariates associated with dispersion (including intercept)
link	link function for abundance covariates
phi.link	link function for dispersion covariates
logpar	Boolean. Defaults to TRUE. Indicator of whether to return log-likelihood.

Value

Negative beta-binomial (log-)likelihood

dbetabinom_cts	<i>Densities of beta binomial distributions, permitting non integer x and size</i>
----------------	---

Description

In some cases we may not have integer W and M 's. In these cases, we can still use corncob to estimate parameters, but we need to think of them as no longer coming from the specific beta binomial parametric model, and instead from an estimating equations framework.

Usage

```
dbetabinom_cts(x, size, prob, rho = 0, log = FALSE)
```

Arguments

x	the value at which defined the density
size	number of trials
prob	the probability of success
rho	the correlation parameter
log	if TRUE, log-densities p are given

Author(s)

Thomas W Yee
 Xiangjie Xue
 Amy D Willis

differentialTest	<i>Identify differentially-abundant and differentially-variable taxa</i>
------------------	--

Description

Identify differentially-abundant and differentially-variable taxa

Usage

```
differentialTest(
  formula,
  phi.formula,
  formula_null,
  phi.formula_null,
  data,
  link = "logit",
  phi.link = "logit",
  test,
  boot = FALSE,
  B = 1000,
  sample_data = NULL,
  taxa_are_rows = TRUE,
  filter_discriminant = TRUE,
  fdr_cutoff = 0.05,
  fdr = "fdr",
  full_output = FALSE,
  inits = NULL,
  inits_null = NULL,
  try_only = NULL,
  verbose = FALSE,
  robust = FALSE,
  ...
)
```

Arguments

formula	an object of class formula without the response: a symbolic description of the model to be fitted to the abundance
phi.formula	an object of class formula without the response: a symbolic description of the model to be fitted to the dispersion
formula_null	Formula for mean under null, without response
phi.formula_null	Formula for overdispersion under null, without response
data	a data frame containing the OTU table, phyloseq, or SummarizedExperiment object containing the variables in the models
link	link function for abundance covariates, defaults to "logit"

<code>phi.link</code>	link function for dispersion covariates, defaults to "logit"
<code>test</code>	Character. Hypothesis testing procedure to use. One of "Wald", "LRT" (likelihood ratio test), or "Rao".
<code>boot</code>	Boolean. Defaults to FALSE. Indicator of whether or not to use parametric bootstrap algorithm. (See pbWald and pBLRT).
<code>B</code>	Optional integer. Number of bootstrap iterations. Ignored if boot is FALSE. Otherwise, defaults to 1000.
<code>sample_data</code>	Data frame or matrix. Defaults to NULL. If data is a data frame or matrix, this must be included as covariates/sample data.
<code>taxa_are_rows</code>	Boolean. Optional. If data is a data frame or matrix, this indicates whether taxa are rows. Defaults to TRUE.
<code>filter_discriminant</code>	Boolean. Defaults to TRUE. If FALSE, discriminant taxa will not be filtered out.
<code>fdr_cutoff</code>	Integer. Defaults to 0.05. Desired false discovery rate.
<code>fdr</code>	Character. Defaults to "fdr". False discovery rate control method, see p.adjust for more options.
<code>full_output</code>	Boolean. Optional. Defaults to FALSE. Indicator of whether to include full bbdml model output for all taxa.
<code>inits</code>	Optional initializations for model fit using formula and phi.formula as rows of a matrix. Defaults to NULL.
<code>inits_null</code>	Optional initializations for model fit using formula_null and phi.formula_null as rows of a matrix. Defaults to NULL.
<code>try_only</code>	Optional numeric. Will try only the try_only taxa, specified either via numeric input or character taxa names. Useful for speed when troubleshooting. Defaults to NULL, testing all taxa.
<code>verbose</code>	Boolean. Defaults to FALSE; print status updates for long-running analyses
<code>robust</code>	Should robust standard errors be used? If not, model-based standard errors are used. Logical, defaults to FALSE.
<code>...</code>	Optional additional arguments for bbdml

Details

See package vignette for details and example usage. Make sure the number of columns in all of the initializations are correct! `inits` probably shouldn't match `inits_null`. To use a contrast matrix, see [contrastsTest](#).

Value

An object of class `differentialTest`. List with elements `p` containing the p-values, `p_fdr` containing the p-values after false discovery rate control, `significant_taxa` containing the taxa names of the statistically significant taxa, `significant_models` containing a list of the model fits for the significant taxa, `all_models` containing a list of the model fits for all taxa, `restrictions_DA` containing a list of covariates that were tested for differential abundance, `restrictions_DV` containing a list of covariates that were tested for differential variability, `discriminant_taxa_DA` containing

the taxa for which at least one covariate associated with the abundance was perfectly discriminant, `discriminant_taxa_DV` containing the taxa for which at least one covariate associated with the dispersion was perfectly discriminant, `data` containing the data used to fit the models. If `full_output = TRUE`, it will also include `full_output`, a list of all model output from `bbdm1`.

Examples

```
# data frame example
data(soil_phylum_small_sample)
data(soil_phylum_small_otu)
da_analysis <- differentialTest(formula = ~ DayAmdmt,
                              phi.formula = ~ DayAmdmt,
                              formula_null = ~ 1,
                              phi.formula_null = ~ DayAmdmt,
                              test = "Wald", boot = FALSE,
                              data = soil_phylum_small_otu,
                              sample_data = soil_phylum_small_sample,
                              fdr_cutoff = 0.05,
                              try_only = 1:5)

# phyloseq example (only run if you have phyloseq installed)
## Not run:
data_phylo <- phyloseq::phyloseq(phyloseq::sample_data(soil_phylum_small_sample),
phyloseq::otu_table(soil_phylum_small_otu, taxa_are_rows = TRUE))
da_analysis <- differentialTest(formula = ~ DayAmdmt,
                              phi.formula = ~ DayAmdmt,
                              formula_null = ~ 1,
                              phi.formula_null = ~ DayAmdmt,
                              test = "Wald", boot = FALSE,
                              data = data_phylo,
                              fdr_cutoff = 0.05,
                              try_only = 1:5)

## End(Not run)
```

doBoot

Function to run a bootstrap iteration

Description

Internal function. Not intended for users.

Usage

```
doBoot(mod, mod_null, test, robust = FALSE)
```

Arguments

mod	an object of class bbdml
mod_null	an object of class bbdml
test	Character. Hypothesis testing procedure to use. One of "Wald" or "LRT" (likelihood ratio test).
robust	Should robust standard errors be used? If not, model-based standard errors are used. Logical, defaults to FALSE.

Value

test statistic from one bootstrap iteration

fishZ	<i>Fisher's z transformation</i>
-------	----------------------------------

Description

Fisher's z transformation

Usage

```
fishZ(x)
```

Arguments

x	data
---	------

Value

Fisher's z transformation of x

Examples

```
x <- .5  
fishZ(x)
```

genInits	<i>Generate initialization for optimization</i>
----------	---

Description

Generate initialization for optimization

Usage

```
genInits(W, M, X, X_star, np, npstar, link, phi.link, nstart = 1, use = TRUE)
```

Arguments

W	Numeric vector of counts
M	Numeric vector of sequencing depth
X	Matrix of covariates associated with abundance (including intercept)
X_star	Matrix of covariates associated with dispersion (including intercept)
np	Number of covariates associated with abundance (including intercept)
npstar	Number of covariates associated with dispersion (including intercept)
link	ink function for abundance covariates
phi.link	ink function for dispersion covariates
nstart	Integer. Defaults to 1. Number of starts for optimization.
use	Boolean. Defaults to TRUE. Indicator of whether to use deterministic initialization.

Value

Matrix of initializations

Examples

```
set.seed(1)
seq_depth <- rpois(20, lambda = 10000)
my_counts <- rbinom(20, size = seq_depth, prob = 0.001) * 10
my_covariate <- cbind(rep(c(0,1), each = 10))
colnames(my_covariate) <- c("X1")

genInits(W = my_counts, M = seq_depth,
  X = cbind(1, my_covariate), X_star = cbind(1, my_covariate),
  np = 2, npstar = 2,
  link = "logit",
  phi.link = "logit", nstart = 2, use = TRUE)
```

getRestrictionTerms	<i>Get index of restricted terms for Wald test</i>
---------------------	--

Description

Created as a convenient helper function. Not intended for users.

Usage

```
getRestrictionTerms(
  mod,
  mod_null = NULL,
  restrictions = NULL,
  restrictions.phi = NULL
)
```

Arguments

mod	an object of class bbdml
mod_null	Optional. An object of class bbdml. Defaults to NULL
restrictions	Optional. Defaults to NULL. Numeric vector indicating the parameters associated with the abundance to test, or character vector with name of variable to test. Note that 1 is the intercept associated with the abundance.
restrictions.phi	Optional. Defaults to NULL. Numeric vector indicating the parameters associated with the dispersion to test, or character vector with name of variable to test. Note that 1 is the intercept associated with the dispersion.

Value

A list with mu representing the index of the restricted covariates associated with abundance and phi representing the index of the restricted covariates associated with the dispersion

gr_full	<i>Parameter Gradient Vector</i>
---------	----------------------------------

Description

Used for internal optimization. Not intended for users.

Usage

```
gr_full(theta, W, M, X, X_star, np, npstar, link, phi.link, logpar = TRUE)
```

Arguments

theta	Numeric vector. Parameters associated with X and X_star
W	Numeric vector of counts
M	Numeric vector of sequencing depth
X	Matrix of covariates associated with abundance (including intercept)
X_star	Matrix of covariates associated with dispersion (including intercept)
np	Number of covariates associated with abundance (including intercept)
npstar	Number of covariates associated with dispersion (including intercept)
link	link function for abundance covariates
phi.link	link function for dispersion covariates
logpar	Boolean. Defaults to TRUE. Indicator of whether to return log-likelihood.

Value

Gradient of likelihood with respect to parameters

HDIbetabinom	<i>Get highest density interval of beta-binomial</i>
--------------	--

Description

Get highest density interval of beta-binomial

Usage

```
HDIbetabinom(percent, M, mu, phi)
```

Arguments

percent	Numeric. Percent interval desired.
M	Numeric vector of sequencing depth
mu	Numeric vector of abundance parameter
phi	Numeric vector of dispersion parameter

Value

List where lower represents the lower bound and upper represents the upper bound

Examples

```
data(soil_phylum_small_otu1)
mod <- bbdml(formula = cbind(W, M - W) ~ DayAmdmt,
phi.formula = ~ DayAmdmt,
data = soil_phylum_small_otu1)
HDIbetabinom(.95, M = mod$M[1], mu = mod$mu.resp[1], phi = mod$phi.resp[1])
```

hessian	<i>Compute Hessian matrix at the MLE</i>
---------	--

Description

Compute Hessian matrix at the MLE

Usage

```
hessian(mod, numerical = FALSE)
```

Arguments

mod	an object of class bbdml
numerical	Boolean. Defaults to FALSE. Indicator of whether to use the numeric Hessian (not recommended).

Value

Hessian matrix at the MLE. In this setting, it's hard to compute expectations to calculate the information matrix, so we return the consistent estimate using sample moments: $\hat{A}(\hat{\theta}) = \sum_i \frac{\partial^2}{\partial \theta \partial \theta^T} l(\theta, W_i)$ evaluated at $\theta = \hat{\theta}$.

Examples

```
data(soil_phylum_small_otu1)
mod <- bbdml(formula = cbind(W, M - W) ~ DayAmdmt,
  phi.formula = ~ DayAmdmt,
  data = soil_phylum_small_otu1)
hessian(mod)
```

ibd_phylo_otu	<i>IBD data, OTU count data frame.</i>
---------------	--

Description

OTU data frame from a phyloseq object from an IBD microbiome study.

Usage

```
ibd_phylo_otu
```

Format

A data frame of OTU counts.

References

- Papa, E., Docktor, M., Smillie, C., Weber, S., Preheim, S. P., Gevers, D., Giannoukos, G., Ciulla, D., Tabbaa, D., Ingram, J., Schauer, D. B., Ward, D. V., Korzenik, J. R., Xavier, R. J., Bousvaros, A., Alm, E. J. & Schauer, D. B. (2012). *Non-invasive mapping of the gastrointestinal microbiota identifies children with inflammatory bowel disease*. PloS One, 7(6), e39242. <doi.org/10.1371/journal.pone.0039242>.
- Duvallet, C., Gibbons, S., Gurry, T., Irizarry, R., & Alm, E. (2017). *MicrobiomeHD: the human gut microbiome in health and disease [Data set]*. Zenodo. <doi.org/10.5281/zenodo.1146764>.

ibd_phylo_sample	IBD data, sample data frame.
------------------	------------------------------

Description

Sample data from a phyloseq object from an IBD microbiome study.

Usage

```
ibd_phylo_sample
```

Format

A data frame of sample data.

References

- Papa, E., Docktor, M., Smillie, C., Weber, S., Preheim, S. P., Gevers, D., Giannoukos, G., Ciulla, D., Tabbaa, D., Ingram, J., Schauer, D. B., Ward, D. V., Korzenik, J. R., Xavier, R. J., Bousvaros, A., Alm, E. J. & Schauer, D. B. (2012). *Non-invasive mapping of the gastrointestinal microbiota identifies children with inflammatory bowel disease*. PloS One, 7(6), e39242. <doi.org/10.1371/journal.pone.0039242>.
- Duvallet, C., Gibbons, S., Gurry, T., Irizarry, R., & Alm, E. (2017). *MicrobiomeHD: the human gut microbiome in health and disease [Data set]*. Zenodo. <doi.org/10.5281/zenodo.1146764>.

ibd_phylo_taxa	IBD data, taxonomy data frame.
----------------	--------------------------------

Description

Taxonomy data from a phyloseq object from an IBD microbiome study.

Usage

```
ibd_phylo_taxa
```

Format

A data frame of taxonomy data.

References

- Papa, E., Docktor, M., Smillie, C., Weber, S., Preheim, S. P., Gevers, D., Giannoukos, G., Ciulla, D., Tabbaa, D., Ingram, J., Schauer, D. B., Ward, D. V., Korzenik, J. R., Xavier, R. J., Bousvaros, A., Alm, E. J. & Schauer, D. B. (2012). *Non-invasive mapping of the gastrointestinal microbiota identifies children with inflammatory bowel disease*. PLoS One, 7(6), e39242. <doi.org/10.1371/journal.pone.0039242>.
- Duvallet, C., Gibbons, S., Gurry, T., Irizarry, R., & Alm, E. (2017). *MicrobiomeHD: the human gut microbiome in health and disease [Data set]*. Zenodo. <doi.org/10.5281/zenodo.1146764>.

invfishZ	<i>Inverse Fisher's z transformation</i>
----------	--

Description

Inverse Fisher's z transformation

Usage

```
invfishZ(x)
```

Arguments

x	data
---	------

Value

Inverse Fisher's z transformation of x

Examples

```
x <- .5
invfishZ(x)
```

invlogit	<i>Inverse logit transformation</i>
----------	-------------------------------------

Description

Inverse logit transformation

Usage

```
invlogit(x)
```

Arguments

x data

Value

Inverse logit transformation of x

Examples

```
x <- .5  
invlogit(x)
```

logit

Logit transformation

Description

Logit transformation

Usage

```
logit(x)
```

Arguments

x data

Value

logit of x

Examples

```
x <- .5  
logit(x)
```

lrtest	<i>Likelihood ratio test</i>
--------	------------------------------

Description

Likelihood ratio test

Usage

```
lrtest(mod, mod_null)
```

Arguments

mod	an object of class bbdml
mod_null	an object of class bbdml, should be nested within mod

Value

P-value from likelihood ratio test.

Examples

```
data(soil_phylum_small_otu1)
mod1 <- bbdml(formula = cbind(W, M - W) ~ DayAmdmt,
  phi.formula = ~ DayAmdmt,
  data = soil_phylum_small_otu1)

mod2 <- bbdml(formula = cbind(W, M - W) ~ 1,
  phi.formula = ~ 1,
  data = soil_phylum_small_otu1)
lrtest(mod1, mod2)
```

objfun	<i>Objective function</i>
--------	---------------------------

Description

Used for internal optimization. Not intended for users.

Usage

```
objfun(theta, W, M, X, X_star, np, npstar, link, phi.link)
```

Arguments

theta	Numeric vector. Parameters associated with X and X_{star}
W	Numeric vector of counts
M	Numeric vector of sequencing depth
X	Matrix of covariates associated with abundance (including intercept)
X_star	Matrix of covariates associated with dispersion (including intercept)
np	Number of covariates associated with abundance (including intercept)
npstar	Number of covariates associated with dispersion (including intercept)
link	link function for abundance covariates
phi.link	link function for dispersion covariates

Value

List of negative log-likelihood, gradient, and hessian

otu_to_taxonomy	<i>Transform OTUs to their taxonomic label</i>
-----------------	--

Description

Transform OTUs to their taxonomic label

Usage

```
otu_to_taxonomy(OTU, data, level = NULL)
```

Arguments

OTU	String vector. Names of OTU labels in data
data	phyloseq object with a taxonomy table
level	(Optional). Character vector. Desired taxonomic levels for output.

Value

String vector. Names of taxonomic labels matching labels of OTU.

otu_to_taxonomy_se	<i>Transform OTUs to their taxonomic label</i>
--------------------	--

Description

Transform OTUs to their taxonomic label

Usage

```
otu_to_taxonomy_se(OTU, data, level = NULL)
```

Arguments

OTU	String vector. Names of OTU labels in data
data	phyloseq object with a taxonomy table
level	(Optional). Character vector. Desired taxonomic levels for output.

Value

String vector. Names of taxonomic labels matching labels of OTU.

pbLRT	<i>Parametric bootstrap likelihood ratio test</i>
-------	---

Description

Parametric bootstrap likelihood ratio test

Usage

```
pbLRT(mod, mod_null, B = 1000)
```

Arguments

mod	an object of class bbdml
mod_null	an object of class bbdml, should be nested within mod
B	Integer. Defaults to 1000. Number of bootstrap iterations.

Value

P-value from parametric bootstrap likelihood ratio test.

Examples

```
data(soil_phylum_small_otu1)
mod1 <- bbdml(formula = cbind(W, M - W) ~ DayAmdmt,
  phi.formula = ~ DayAmdmt,
  data = soil_phylum_small_otu1)

mod2 <- bbdml(formula = cbind(W, M - W) ~ 1,
  phi.formula = ~ 1,
  data = soil_phylum_small_otu1)
pbLRT(mod1, mod2, B = 50)
```

pbRao

*Parametric bootstrap Rao test***Description**

Parametric bootstrap Rao test

Usage

```
pbRao(mod, mod_null, B = 1000)
```

Arguments

mod	an object of class bbdml
mod_null	an object of class bbdml, should be nested within mod
B	Integer. Defaults to 1000. Number of bootstrap iterations.

Value

P-value from parametric bootstrap Rao test.

Examples

```
data(soil_phylum_small_otu1)
mod1 <- bbdml(formula = cbind(W, M - W) ~ DayAmdmt,
  phi.formula = ~ DayAmdmt,
  data = soil_phylum_small_otu1)

mod2 <- bbdml(formula = cbind(W, M - W) ~ 1,
  phi.formula = ~ 1,
  data = soil_phylum_small_otu1)
pbRao(mod1, mod2, B = 10)
```

pbWald	<i>Parametric bootstrap Wald test</i>
--------	---------------------------------------

Description

Parametric bootstrap Wald test

Usage

```
pbWald(mod, mod_null, B = 1000, robust = FALSE)
```

Arguments

mod	an object of class bbdml
mod_null	an object of class bbdml, should be nested within mod
B	Integer. Defaults to 1000. Number of bootstrap iterations.
robust	Should robust standard errors be used? If not, model-based standard errors are used. Logical, defaults to FALSE.

Value

P-value from parametric bootstrap Wald test.

Examples

```
data(soil_phylum_small_otu1)
mod1 <- bbdml(formula = cbind(W, M - W) ~ DayAmdmt,
  phi.formula = ~ DayAmdmt,
  data = soil_phylum_small_otu1)

mod2 <- bbdml(formula = cbind(W, M - W) ~ 1,
  phi.formula = ~ 1,
  data = soil_phylum_small_otu1)
pbWald(mod1, mod2, B = 50)
```

plot.bbdml	<i>Plotting function</i>
------------	--------------------------

Description

Plotting function

Usage

```
## S3 method for class 'bbdml'
plot(
  x,
  total = FALSE,
  color = NULL,
  shape = NULL,
  facet = NULL,
  title = NULL,
  B = 1000,
  sample_names = TRUE,
  data_only = FALSE,
  ...
)
```

Arguments

x	Object of class bbdml.
total	(Optional). Default FALSE. Boolean indicator for whether to plot on total counts scale
color	(Optional). Default NULL. The sample variable to map to different colors. Can be a single character string of the variable name in <code>sample_data</code> or a custom supplied vector with length equal to the number of samples. Use a character vector to have ggplot2 default.
shape	(Optional). Default NULL. The sample variable to map to different shapes. Can be a single character string of the variable name in <code>sample_data</code> or a custom supplied vector with length equal to the number of samples.
facet	(Optional). Default NULL. The sample variable to map to different panels in a facet grid. Must be a single character string of a variable name in <code>sample_data</code> .
title	(Optional). Default NULL. Character string. The main title for the graphic.
B	(Optional). Default 1000. Integer. Number of bootstrap simulations for prediction intervals. Use <code>B = 0</code> for no prediction intervals.
sample_names	(Optional). Default TRUE. Boolean. If FALSE, remove sample names from the plot.
data_only	(Optional). Default FALSE. Boolean. If TRUE, only returns data frame.
...	There are no optional parameters at this time.

Value

Object of class ggplot. Plot of bbdml model fit with 95

Examples

```
data(soil_phylum_small_otu1)
mod <- bbdml(formula = cbind(W, M - W) ~ DayAmdmt,
  phi.formula = ~ DayAmdmt,
```

```
data = soil_phylum_small_otu1)
# Here we use B = 50 for quick demonstration purposes.
# In practice, we recommend a higher value for B for more accurate intervals
plot(mod, color = "DayAmdmt", B = 50)
```

plot.differentialTest *differentialTest plot function*

Description

differentialTest plot function

Usage

```
## S3 method for class 'differentialTest'
plot(x, level = NULL, data_only = FALSE, ...)
```

Arguments

x	Object of class differentialTest
level	(Optional). Character vector. Desired taxonomic levels for taxa labels.
data_only	(Optional). Default FALSE. Boolean. If TRUE, only returns data frame.
...	No optional arguments are accepted at this time.

Value

Object of class ggplot. Plot of coefficients from models for significant taxa from differentialTest

Examples

```
# phyloseq example
data(soil_phylum_small_sample)
data(soil_phylum_small_otu)
da_analysis <- differentialTest(formula = ~ DayAmdmt,
                               phi.formula = ~ DayAmdmt,
                               formula_null = ~ 1,
                               phi.formula_null = ~ DayAmdmt,
                               test = "Wald", boot = FALSE,
                               data = soil_phylum_small_otu,
                               sample_data = soil_phylum_small_sample,
                               fdr_cutoff = 0.05,
                               try_only = 1:5)

plot(da_analysis, level = "Phylum")
```

print.bbdml	<i>Print function</i>
-------------	-----------------------

Description

Print function

Usage

```
## S3 method for class 'bbdml'
print(
  x,
  digits = max(3L, getOption("digits") - 3L),
  signif.stars = getOption("show.signif.stars"),
  ...
)
```

Arguments

x	Object of class bbdml
digits	the number of significant digits to use when printing.
signif.stars	logical. If TRUE, ‘significance stars’ are printed for each coefficient.
...	No optional arguments are accepted at this time.

Value

NULL. Displays printed model summary.

Examples

```
data(soil_phylum_small_otu1)
mod <- bbdml(formula = cbind(W, M - W) ~ DayAmdmt,
  phi.formula = ~ DayAmdmt,
  data = soil_phylum_small_otu1)
print(mod)
```

print.differentialTest	<i>differentialTest print function</i>
------------------------	--

Description

differentialTest print function

Usage

```
## S3 method for class 'differentialTest'
print(x, ...)
```

Arguments

```
x                Object of class bbdml
...              No optional arguments are accepted at this time.
```

Value

NULL. Displays printed differentialTest summary.

Examples

```
# phyloseq example
data(soil_phylum_small_sample)
data(soil_phylum_small_otu)
da_analysis <- differentialTest(formula = ~ DayAmdmt,
                                phi.formula = ~ DayAmdmt,
                                formula_null = ~ 1,
                                phi.formula_null = ~ DayAmdmt,
                                test = "Wald", boot = FALSE,
                                data = soil_phylum_small_otu,
                                sample_data = soil_phylum_small_sample,
                                fdr_cutoff = 0.05,
                                try_only = 1:5)

print(da_analysis)
```

```
print.summary.bbdml    Print summary function
```

Description

Print summary function

Usage

```
## S3 method for class 'summary.bbdml'
print(
  x,
  digits = max(3L, getOption("digits") - 3L),
  signif.stars = getOption("show.signif.stars"),
  ...
)
```

Arguments

x	Object of class bbdml
digits	the number of significant digits to use when printing.
signif.stars	logical. If TRUE, 'significance stars' are printed for each coefficient.
...	No optional arguments are accepted at this time.

Value

NULL. Displays printed model summary.

Examples

```
data(soil_phylum_small_otu1)
mod <- bbdml(formula = cbind(W, M - W) ~ DayAmdmt,
  phi.formula = ~ DayAmdmt,
  data = soil_phylum_small_otu1)
print(summary(mod))
```

qbetabinom	<i>Get quantiles of beta binom</i>
------------	------------------------------------

Description

Get quantiles of beta binom

Usage

```
qbetabinom(p, M, mu, phi)
```

Arguments

p	Numeric. Probability for quantile
M	Numeric vector of sequencing depth
mu	Numeric vector of abundance parameter
phi	Numeric vector of dispersion parameter

Value

quantile

Examples

```
data(soil_phylum_small_otu1)
mod <- bbdml(formula = cbind(W, M - W) ~ DayAmdmt,
  phi.formula = ~ DayAmdmt,
  data = soil_phylum_small_otu1)
qbetabinom(.5, M = mod$M[1], mu = mod$mu.resp[1], phi = mod$phi.resp[1])
```

raotest	<i>Rao-type chi-squared test (model-based or robust)</i>
---------	--

Description

Rao-type chi-squared test (model-based or robust)

Usage

```
raotest(mod, mod_null)
```

Arguments

mod	an object of class bbdml
mod_null	an object of class bbdml, should be nested within mod

Value

P-value from likelihood ratio test.

Examples

```
data(soil_phylum_small_otu1)
mod1 <- bbdml(formula = cbind(W, M - W) ~ DayAmdmt,
  phi.formula = ~ DayAmdmt,
  data = soil_phylum_small_otu1)

mod2 <- bbdml(formula = cbind(W, M - W) ~ 1,
  phi.formula = ~ 1,
  data = soil_phylum_small_otu1)
raotest(mod1, mod2)
```

sand_vcov	<i>Compute sandwich estimate of variance-covariance matrix</i>
-----------	--

Description

Compute sandwich estimate of variance-covariance matrix

Usage

```
sand_vcov(mod, numerical = FALSE)
```

Arguments

mod	an object of class bbdml
numerical	Boolean. Defaults to FALSE. Indicator of whether to use the numeric Hessian and score (not recommended).

Value

Sandwich variance-covariance matrix. $\hat{A}^{-1}\hat{B}\hat{A}^{-1}$.

Examples

```
data(soil_phylum_small_otu1)
mod <- bbdml(formula = cbind(W, M - W) ~ DayAmdmt,
  phi.formula = ~ DayAmdmt,
  data = soil_phylum_small_otu1)
sand_vcov(mod)
```

sandSE	<i>Compute sandwich standard errors. Legacy function. Use sand_vcov instead.</i>
--------	--

Description

Compute sandwich standard errors. Legacy function. Use sand_vcov instead.

Usage

```
sandSE(mod, numerical = FALSE)
```

Arguments

mod	an object of class bbdml
numerical	Boolean. Defaults to FALSE. Indicator of whether to use the numeric Hessian and score (not recommended).

Value

Sandwich variance-covariance matrix

Examples

```
data(soil_phylum_small_otu1)
mod <- bbdml(formula = cbind(W, M - W) ~ DayAmdmt,
  phi.formula = ~ DayAmdmt,
  data = soil_phylum_small_otu1)
sandSE(mod)
```

score	<i>Compute score at the MLE</i>
-------	---------------------------------

Description

Compute score at the MLE

Usage

```
score(mod, numerical = FALSE, get_score_covariance = FALSE)
```

Arguments

mod	an object of class bbdml
numerical	Boolean. Defaults to FALSE. Indicator of whether to use the numeric Hessian and score (not recommended).
get_score_covariance	Boolean. Defaults to FALSE. Should we return a robust estimate of variance of score: $\hat{B}(\hat{\theta}) = \sum_i G(\hat{\theta}; W_i)G(\hat{\theta}; W_i)^T$. This parameter is not intended for users.

Value

Score at the MLE. For $G(\theta, w)$ score function, returns $\sum_i G(\hat{\theta}, W_i)$ if `get_score_covariance = FALSE`.

Examples

```
data(soil_phylum_small_otu1)
mod <- bbdml(formula = cbind(W, M - W) ~ DayAmdmt,
  phi.formula = ~ DayAmdmt,
  data = soil_phylum_small_otu1)
score(mod)
```

simulate.bbdml	<i>Simulate from beta-binomial model</i>
----------------	--

Description

Simulate from beta-binomial model

Usage

```
## S3 method for class 'bbdml'
simulate(object, nsim, seed = NULL, ...)
```

Arguments

- object an object of class bbdml
- nsim Integer. Number of simulations
- seed Optional integer to set a random seed
- ... There are no additional parameters at this time.

Value

nsim simulations from object

soil_phylo_otu	<i>Soil data, otu table as data frame.</i>
----------------	--

Description

A data frame made from a soil ‘phyloseq’ object with only otu count data.

Usage

soil_phylo_otu

Format

A phyloseq-class experiment-level object with an OTU table.

otu_table OTU table with 7,770 taxa and 119 samples

References

Whitman, T., Pepe-Ranney, C., Enders, A., Koechli, C., Campbell, A., Buckley, D. H., Lehmann, J. (2016). *Dynamics of microbial community composition and soil organic carbon mineralization in soil following addition of pyrogenic and fresh organic matter*. The ISME journal, 10(12):2918. <doi: 10.1038/ismej.2016.68>.

soil_phylo_sample	<i>Soil data, sample data.</i>
-------------------	--------------------------------

Description

A data frame made from a soil ‘phyloseq’ object with only sample data.

Usage

```
soil_phylo_sample
```

Format

A phyloseq-class experiment-level object with sample data.

sam_data sample data with the following covariates:

- Plants, values 0 and 1. Index for different plants
- Day, values 0 (initial sampling point), 1 (12 days after treatment additions), and 2 (82 days after treatment additions). Index for different days of measurement
- Amdmt, values 0 (no additions), 1 (biochar additions), and 2 (fresh biomass additions). Index for different soil additives.
- DayAmdmt, values 00, 01, 02, 10, 11, 12, 20, 21, and 22. A single index for the combination of Day and Amdmt with Day as the first digit and Amdmt as the second digit.
- ID, values A, B, C, D, and F. Index for different soil plots.

References

Whitman, T., Pepe-Ranney, C., Enders, A., Koechli, C., Campbell, A., Buckley, D. H., Lehmann, J. (2016). *Dynamics of microbial community composition and soil organic carbon mineralization in soil following addition of pyrogenic and fresh organic matter*. The ISME journal, 10(12):2918. <doi: 10.1038/ismej.2016.68>.

soil_phylo_taxa	<i>Soil data, taxa table as data frame.</i>
-----------------	---

Description

A data frame made from a soil ‘phyloseq’ object with only taxonomy data.

Usage

```
soil_phylo_taxa
```

Format

A phyloseq-class experiment-level object with an OTU table.

tax_table taxonomy table

References

Whitman, T., Pepe-Ranney, C., Enders, A., Koechli, C., Campbell, A., Buckley, D. H., Lehmann, J. (2016). *Dynamics of microbial community composition and soil organic carbon mineralization in soil following addition of pyrogenic and fresh organic matter*. The ISME journal, 10(12):2918. <doi: 10.1038/ismej.2016.68>.

soil_phylum_contrasts_otu

Small soil phylum data for contrasts examples, otu table as data frame

Description

A small subset of [soil_phylo_otu](#) used for examples of testing contrasts. A data frame made from the 'phyloseq' object with only otu counts.

Usage

```
soil_phylum_contrasts_otu
```

Format

A phyloseq-class experiment-level object with an OTU table.

otu_table OTU table with 39 taxa and 56 samples

References

Whitman, T., Pepe-Ranney, C., Enders, A., Koechli, C., Campbell, A., Buckley, D. H., Lehmann, J. (2016). *Dynamics of microbial community composition and soil organic carbon mineralization in soil following addition of pyrogenic and fresh organic matter*. The ISME journal, 10(12):2918. <doi: 10.1038/ismej.2016.68>.

`soil_phylum_contrasts_sample`

Small soil phylum data for contrasts examples, sample data as data frame

Description

A small subset of `soil_phylo_sample` used for examples of testing contrasts. A data frame made from the ‘phyloseq’ object with only sample data.

Usage

`soil_phylum_contrasts_sample`

Format

A phyloseq-class experiment-level object with sample data.

sam_data sample data with the following covariates:

- Plants, values 0 and 1. Index for different plants
- Day, values 0 (initial sampling point), 1 (12 days after treatment additions), and 2 (82 days after treatment additions). Index for different days of measurement
- Amdmt, values 0 (no additions), 1 (biochar additions), and 2 (fresh biomass additions). Index for different soil additives.
- DayAmdmt, values 00, 01, 02, 10, 11, 12, 20, 21, and 22. A single index for the combination of Day and Amdmt with Day as the first digit and Amdmt as the second digit.
- ID, values A, B, C, D, and F. Index for different soil plots.

References

Whitman, T., Pepe-Ranne, C., Enders, A., Koechli, C., Campbell, A., Buckley, D. H., Lehmann, J. (2016). *Dynamics of microbial community composition and soil organic carbon mineralization in soil following addition of pyrogenic and fresh organic matter*. The ISME journal, 10(12):2918. <doi: 10.1038/ismej.2016.68>.

`soil_phylum_small_otu` *Small soil phylum data for examples, otu table as data frame*

Description

A small subset of `soil_phylo_otu` used for examples. A data frame made from the ‘phyloseq’ object with only otu counts.

Usage

`soil_phylum_small_otu`

Format

A phyloseq-class experiment-level object with an OTU table.

otu_table OTU table with 39 taxa and 32 samples

References

Whitman, T., Pepe-Ranne, C., Enders, A., Koechli, C., Campbell, A., Buckley, D. H., Lehmann, J. (2016). *Dynamics of microbial community composition and soil organic carbon mineralization in soil following addition of pyrogenic and fresh organic matter*. The ISME journal, 10(12):2918. <doi: 10.1038/ismej.2016.68>.

soil_phylum_small_otu1

Small soil phylum data for examples, sample data as data frame combined with counts for OTU 1 and sequencing depth.

Description

A small subset of [soil_phylo_sample](#) used for examples. A data frame made from the ‘phyloseq’ object with only sample data and counts for OTU 1.

Usage

```
soil_phylum_small_otu1
```

Format

A phyloseq-class experiment-level object with sample data and OTU 1 counts.

sam_data sample data with the following covariates:

- Plants, values 0 and 1. Index for different plants
- Day, values 0 (initial sampling point), 1 (12 days after treatment additions), and 2 (82 days after treatment additions). Index for different days of measurement
- Amdmt, values 0 (no additions), 1 (biochar additions), and 2 (fresh biomass additions). Index for different soil additives.
- DayAmdmt, values 00, 01, 02, 10, 11, 12, 20, 21, and 22. A single index for the combination of Day and Amdmt with Day as the first digit and Amdmt as the second digit.
- ID, values A, B, C, D, and F. Index for different soil plots.
- W, counts for OTU1 in each sample. This OTU corresponds with the phylum *Proteobacteria*.
- M, the sequencing depth for each sample.

References

Whitman, T., Pepe-Ranne, C., Enders, A., Koechli, C., Campbell, A., Buckley, D. H., Lehmann, J. (2016). *Dynamics of microbial community composition and soil organic carbon mineralization in soil following addition of pyrogenic and fresh organic matter*. The ISME journal, 10(12):2918. <doi: 10.1038/ismej.2016.68>.

soil_phylum_small_sample

Small soil phylum data for examples, sample data as data frame

Description

A small subset of [soil_phylo_sample](#) used for examples. A data frame made from the ‘phyloseq’ object with only sample data.

Usage

```
soil_phylum_small_sample
```

Format

A phyloseq-class experiment-level object with sample data.

sam_data sample data with the following covariates:

- Plants, values 0 and 1. Index for different plants
- Day, values 0 (initial sampling point), 1 (12 days after treatment additions), and 2 (82 days after treatment additions). Index for different days of measurement
- Amdmt, values 0 (no additions), 1 (biochar additions), and 2 (fresh biomass additions). Index for different soil additives.
- DayAmdmt, values 00, 01, 02, 10, 11, 12, 20, 21, and 22. A single index for the combination of Day and Amdmt with Day as the first digit and Amdmt as the second digit.
- ID, values A, B, C, D, and F. Index for different soil plots.

References

Whitman, T., Pepe-Ranne, C., Enders, A., Koechli, C., Campbell, A., Buckley, D. H., Lehmann, J. (2016). *Dynamics of microbial community composition and soil organic carbon mineralization in soil following addition of pyrogenic and fresh organic matter*. The ISME journal, 10(12):2918. <doi: 10.1038/ismej.2016.68>.

summary.bbdml	<i>Summary function</i>
---------------	-------------------------

Description

Summary function

Usage

```
## S3 method for class 'bbdml'
summary(object, ...)
```

Arguments

object	Object of class bbdml
...	No optional arguments are accepted at this time.

Value

Object of class summary.bbdml. Displays printed model summary.

Examples

```
data(soil_phylum_small_otu1)
mod <- bbdml(formula = cbind(W, M - W) ~ DayAmdmt,
  phi.formula = ~ DayAmdmt,
  data = soil_phylum_small_otu1)
summary(mod)
```

waldchisq	<i>Wald-type chi-squared test</i>
-----------	-----------------------------------

Description

Wald-type chi-squared test

Usage

```
waldchisq(
  mod,
  mod_null = NULL,
  restrictions = NULL,
  restrictions.phi = NULL,
  contrasts_DA = NULL,
  contrasts_DV = NULL,
  robust = FALSE
)
```

Arguments

<code>mod</code>	an object of class <code>bbdml</code>
<code>mod_null</code>	Optional. An object of class <code>bbdml</code> , should be nested within <code>mod</code> . If not included, need to include <code>restrictions</code> or <code>restrictions.phi</code> .
<code>restrictions</code>	Optional. Defaults to <code>NULL</code> . Numeric vector indicating the parameters associated with the abundance to test, or character vector with name of variable to test. Note that 1 is the intercept associated with the abundance.
<code>restrictions.phi</code>	Optional. Defaults to <code>NULL</code> . Numeric vector indicating the parameters associated with the dispersion to test, or character vector with name of variable to test. Note that 1 is the intercept associated with the dispersion.
<code>contrasts_DA</code>	List. Optional. Constructs a contrast matrix. List elements should be characters specifying contrasts in the parameters within formula. Note that this is only available with "Wald" value for test.
<code>contrasts_DV</code>	List. Optional. Constructs a contrast matrix. List elements should be characters specifying contrasts in the parameters within <code>phi.formula</code> . Note that this is only available with "Wald" value for test.
<code>robust</code>	Should robust standard errors be used? If not, model-based standard errors are used. Logical, defaults to <code>FALSE</code> .

Value

Matrix with wald test statistics and p-values. Only performs univariate tests.

P-value from Wald test.

Examples

```
data(soil_phylum_small_otu1)
mod1 <- bbdml(formula = cbind(W, M - W) ~ DayAmdmt,
  phi.formula = ~ DayAmdmt,
  data = soil_phylum_small_otu1)

mod2 <- bbdml(formula = cbind(W, M - W) ~ 1,
  phi.formula = ~ 1,
  data = soil_phylum_small_otu1)

# Example using mod_null
waldchisq(mod = mod1, mod_null = mod2)
waldchisq(mod = mod1, mod_null = mod2, robust = TRUE)

# Example using restrictions and restrictions.phi
waldchisq(mod = mod1, restrictions = 2, restrictions.phi = 2)
waldchisq(mod = mod1, restrictions = "DayAmdmt", restrictions.phi = "DayAmdmt")
waldchisq(mod = mod1, restrictions = 2, restrictions.phi = "DayAmdmt")
waldchisq(mod = mod1, restrictions = 2, restrictions.phi = 2, robust = TRUE)
```

waldchisq_test	<i>Wald-type chi-squared test statistic (model-based or robust)</i>
----------------	---

Description

This is a helper function and not intended for users

Usage

```
waldchisq_test(
  mod,
  restrictions = NULL,
  restrictions.phi = NULL,
  contrasts_DA = NULL,
  contrasts_DV = NULL,
  robust = FALSE
)
```

Arguments

mod	an object of class bbdml
restrictions	Optional. Defaults to NULL. Numeric vector indicating the parameters associated with the abundance to test, or character vector with name of variable to test. Note that 1 is the intercept associated with the abundance.
restrictions.phi	Optional. Defaults to NULL. Numeric vector indicating the parameters associated with the dispersion to test, or character vector with name of variable to test. Note that 1 is the intercept associated with the dispersion.
contrasts_DA	List. Optional. Constructs a contrast matrix. List elements should be characters specifying contrasts in the parameters within formula. Note that this is only available with "Wald" value for test.
contrasts_DV	List. Optional. Constructs a contrast matrix. List elements should be characters specifying contrasts in the parameters within phi.formula. Note that this is only available with "Wald" value for test.
robust	Should robust standard errors be used? If not, model-based standard errors are used. Logical, defaults to FALSE.

Value

Test statistic for Wald test.

walddt	<i>Wald-type t test (model-based or robust)</i>
--------	---

Description

Wald-type t test (model-based or robust)

Usage

```
walddt(mod)
```

Arguments

mod an object of class bbdml

Value

Matrix with wald test statistics and p-values. Only performs univariate tests.

Examples

```
data(soil_phylum_small_otu1)
mod <- bbdml(formula = cbind(W, M - W) ~ DayAmdmt,
  phi.formula = ~ DayAmdmt,
  data = soil_phylum_small_otu1)
walddt(mod)
```

warn_phyloseq	<i>Function to throw error if the ‘phyloseq’ package is called but it is not installed</i>
---------------	--

Description

Function to throw error if the ‘phyloseq’ package is called but it is not installed

Usage

```
warn_phyloseq()
```

warn_sumexp	<i>Function to throw error if the ‘SummarizedExperiment’ package is called but it is not installed</i>
-------------	--

Description

Function to throw error if the ‘SummarizedExperiment’ package is called but it is not installed

Usage

```
warn_sumexp()
```

Index

* datasets

- ibd_phylo_otu, [20](#)
- ibd_phylo_sample, [21](#)
- ibd_phylo_taxa, [21](#)
- soil_phylo_otu, [37](#)
- soil_phylo_sample, [38](#)
- soil_phylo_taxa, [38](#)
- soil_phylum_contrasts_otu, [39](#)
- soil_phylum_contrasts_sample, [40](#)
- soil_phylum_small_otu, [40](#)
- soil_phylum_small_otu1, [41](#)
- soil_phylum_small_sample, [42](#)

bbdml, [3](#), [8](#), [14](#)

checkNested, [5](#)

clean_taxa_names, [6](#)

clean_taxa_names_se, [6](#)

contrastsTest, [7](#), [14](#)

convert_phylo, [9](#)

convert_sumexp, [10](#)

corncob (corncob-package), [3](#)

corncob-package, [3](#)

coth, [10](#)

dbetabin, [11](#)

dbetabin_neg, [11](#)

dbetabinom_cts, [12](#)

differentialTest, [8](#), [13](#)

doBoot, [15](#)

fishZ, [16](#)

genInits, [17](#)

getRestrictionTerms, [18](#)

gr_full, [18](#)

HDIbetabinom, [19](#)

hessian, [20](#)

ibd_phylo_otu, [20](#)

ibd_phylo_sample, [21](#)

ibd_phylo_taxa, [21](#)

invfishZ, [22](#)

invlogit, [22](#)

logit, [23](#)

lrtest, [24](#)

objfun, [24](#)

optimr, [4](#)

otu_to_taxonomy, [25](#)

otu_to_taxonomy_se, [26](#)

p.adjust, [8](#), [14](#)

pbLRT, [14](#), [26](#)

pbRao, [27](#)

pbWald, [14](#), [28](#)

plot.bbdml, [28](#)

plot.differentialTest, [30](#)

print.bbdml, [31](#)

print.differentialTest, [31](#)

print.summary.bbdml, [32](#)

qbetabinom, [33](#)

raotest, [34](#)

sand_vcov, [34](#)

sandSE, [35](#)

score, [36](#)

simulate.bbdml, [36](#)

soil_phylo_otu, [37](#), [39](#), [40](#)

soil_phylo_sample, [38](#), [40–42](#)

soil_phylo_taxa, [38](#)

soil_phylum_contrasts_otu, [39](#)

soil_phylum_contrasts_sample, [40](#)

soil_phylum_small_otu, [40](#)

soil_phylum_small_otu1, [41](#)

soil_phylum_small_sample, [42](#)

summary.bbdml, [43](#)

trust, [4](#)

waldchisq, [43](#)

waldchisq_test, [45](#)

waldt, [46](#)

warn_phyloseq, [46](#)

warn_sumexp, [47](#)